# Enabling Technology Transforms a Prototype GNSS Interferometric Reflectometry (GNSS-IR) System to Global Operation






# Outline

- GNSS Interferometric Reflectometry (GNSS-IR)
- Prototype system and challenges for globalization
- Automated evaluator of candidate site characteristics
- Automated site submission portal
- Framework for process management
- Architecture to enable cloud operations

# Why use ground GPS to estimate hydrologic variables?

- 1. Snow Depth and SWE
- 2. Soil moisture
- 3. Vegetation Water Content



### **Advantages**


- Extensive infrastructure exists
- Data freely available
- Same frequency as satellites
- Supplement other *in situ* sensors
- ~1000 m² footprint intermediate in scale
- Daily estimates or better


## Negatives


260°

- Antenna not designed for reflections
- Site conditions vary

2/0








Larson et al., 2008 (GRL); Larson et al., 2009 (GRL); Larson and Small, 2014 (JSTARS)

# From Regional to Global



International Soil Moisture Network


**Public GNSS sites** 

PBO H2O pilot project


The PBO-H<sub>2</sub>O prototype was purpose-built for the largely homogenous PBO network, but there are many more subnetworks available.

# Station Evaluator – site characteristics

Software searches online sources and produces a human-readable report, or machine-readable JSON output.




# Station Evaluator – site characteristics



# Station Evaluator – site characteristics


Station Evaluator is available for licensing from JPL/Caltech.




- $\bullet\,$  (c) OpenStreetMap contributors. Data available under Open Database License.
- ORNL DAAC 2017. MODIS Collection 6 Land Products Global Subsetting and Visualization Tool. ORNL DAAC, Oak Ridge, Tennessee, USA. Accessed 2017-04-13. Subset obtained for MCD12Q1 product at 34.2214,-118.1095, time period 2001001-2002001, and subset size: 1X1km
- This material is based on data services provided by the OpenTopography Facility with support from the National Science Foundation under NSF Award Numbers 1226353 & 1225810

#### **Appendix: JSON output**


 $\{"100m\_relief\_m": "87.0", "50m\_relief\_m": "51.08", "elev\_m": "1366.68129022", "generator": "eval\_characteristics.py", "landcover": {"IGBP\_type": "8.0", "name": "Woody Savannas"}, "landcover_1km": [{"IGBP type": "7", "name": "Open shrublands"}, {"IGBP type": "8", "name": "Woody Savannas"}, {"IGBP type": "9", "name": "Savannas"}, {"IGBP type": "12", "name": "Coplands"}], "lat": "34.221391", "location": {"2": "United States of America", "4": "California", "6": "Los Angeles County"}, "lon": "-118.109486", "name": "INSP", "objects_50m": {"quadrants": ["1", "3", "4"], "range\_m": "23", "tags": [{"sac\_scale": "hiking"}, {"name": "Castle Canyon Trail"}, {"highway": "path"}]}, {"quadrants": ["1", "4"], "range\_m": "27", "tags": [{"name": "One Man & Mule Trail"}, {"highway": "track"}]}, {"quadrants": ["1", "2"], "range\_m": "23", "tags": [{"building": "yes"}, {"name": "Inspiration Point Paviillion"}]}, {"quadrants": ["1", "2"], "range\_m": "27", "tags": [{"sac\_scale": "hiking"}, {"quadrants": ["1", "2"], "range\_m": "27", "tags": [{"sac\_scale": "hiking"}, {"quadrants": "1", "2", "range\_m": "27", "tags": [{"sac\_scale": "hiking"}, {"quadrants": ["1", "2"], "range\_m": "27", "tags": ["sac\_scale": "hiking"}, {"name": "Fire Road"}, {"highway": "track"}]}, {"quadrants": ["1", "2", "4"], "range\_m": "38", "tags": [{"sac\_scale": "hiking"}, {"name": "Fire Road"}, {"highway": "track"}]}}, {"quadrants": ["1", "2", "4"], "range\_m": "38", "tags": []}]}$ 




# **Vegetation Evaluator Test**




Evaluator recommends these, in agreement with a human




# **Vegetation Evaluator Test**




Evaluator recommends against these, which were also deselected by a human



# Demonstration of site submission automation



# Demonstration of site submission automation




# Containerization strategy

Deployable on any platform (cluster, cloud, hybrid cloud, laptop...)

Code was refactored into Apache OODT, an adaptable framework for ingestion, management, processing, and distribution of science data

#### **DOCKER OODT 1.0 ARCHITECTURE FOR GNSS H20**



# Summary

- GNSS-IR measures snow, soil moisture, and vegetation fluctuations over an area ~1000 m<sup>2</sup>
- A prototype western-U.S. system is currently available (http://gnss-h2o.jpl.nasa.gov)
- Technology to enable globalizing the project has been developed
  - Automated evaluator of site physical and data characteristics
  - Portal for submission of candidate new sites
  - OODT framework for process management
  - Containerized architecture permits cloud operations

Thank you: NSF, UNAVCO, NASA